



*Able Label stocks 4" O.D. or 5" O.D. by 1" Core label rolls which can be used with printer models with a maximum roll O.D. of 5.0".  
Able Label can also provide all of our products on any core, O.D. or wind direction desired. Call 800.348.1455 for quote.*

DATAMAX PRINTERS			MEDIA/LABEL SPECIFICATIONS (O.D.: OUTSIDE DIAMETER ~ I.D.: INSIDE DIAMETER)					RIBBON SPECIFICATIONS			
Model	Print Method	Printer Type	Maximum Roll O.D.	Core I.D.	Min Width	Max Width	Max Print Width	Max Width	Max Length	Ink Wind	Core I.D.
A-4212 Mark II	DT or TT	Print Engine	Please refer to product manual.		1.0"	4.65"	4.1"	No Info	2,132' (650 m)	CSI or CSO	1.0"
A-4310 Mark II	DT or TT	Print Engine	Please refer to product manual.		1.0"	4.65"	4.2"	No Info	2,132' (650 m)	CSI or CSO	1.0"
A-4408 Mark II	DT or TT	Print Engine	Please refer to product manual.		1.0"	4.65"	4.1"	No Info	2,132' (650 m)	CSI or CSO	1.0"
A-4606 Mark II	DT or TT	Print Engine	Please refer to product manual.		1.0"	4.65"	4.2"	No Info	2,132' (650 m)	CSI or CSO	1.0"
A-6212 Mark II	DT or TT	Print Engine	Please refer to product manual.		2.0"	6.7"	6.6"	No Info	2,132' (650 m)	CSI or CSO	1.0"
A-6310 Mark II	DT or TT	Print Engine	Please refer to product manual.		2.0"	6.7"	6.4"	No Info	2,132' (650 m)	CSI or CSO	1.0"
Allegro 2	DT or TT	Industrial	8.0"	3.0"	1.0"	4.65"	4.1"	No Info	1,182' (360 m)	CSI	1.0"
H-4212	DT or TT	Industrial	8.0"	3.0"	1.0"	4.65"	4.09"	4.5"	1,968' (600 m)	CSI or CSO	1.0"
H-4408	DT or TT	Industrial	8.0"	3.0"	1.0"	4.65"	4.09"	4.5"	1,968' (600 m)	CSI or CSO	1.0"
H-4310	DT or TT	Industrial	8.0"	3.0"	1.0"	4.65"	4.16"	4.5"	1,968' (600 m)	CSI or CSO	1.0"
H-4606	DT or TT	Industrial	8.0"	3.0"	1.0"	4.65"	4.16"	4.5"	1,968' (600 m)	CSI or CSO	1.0"
H-6210	DT or TT	Industrial	8.0"	3.0"	2.0"	6.70"	6.61"	6.7"	1,968' (600 m)	CSI or CSO	1.0"
H-6308	DT or TT	Industrial	8.0"	3.0"	2.0"	6.70"	6.40"	6.7"	1,968' (600 m)	CSI or CSO	1.0"
I-4212e Mark II	DT or TT	Industrial	8.0"	3.0"	1.0"	4.70"	4.10"	4.5"	1,968' (600 m)	CSI or CSO	1.0"
I-4310 Mark II	DT or TT	Industrial	8.0"	3.0"	1.0"	4.70"	4.16"	4.5"	1,968' (600 m)	CSI or CSO	1.0"
I-4606 Mark II	DT or TT	Industrial	8.0"	3.0"	1.0"	4.70"	4.16"	4.5"	1,968' (600 m)	CSI or CSO	1.0"
I-4206	DT or TT	Industrial	8.0"	3.0"	1.0"	4.65"	4.10"	4.5"	1,968' (600 m)	CSI	1.0"
I-4208	DT or TT	Industrial	8.0"	3.0"	1.0"	4.65"	4.10"	4.5"	1,968' (600 m)	CSI	1.0"
I-4210	DT or TT	Industrial	8.0"	3.0"	1.0"	4.65"	4.10"	4.5"	1,968' (600 m)	CSI	1.0"
I-4212	DT or TT	Industrial	8.0"	3.0"	1.0"	4.65"	4.10"	4.5"	1,968' (600 m)	CSI	1.0"
I-4308	DT or TT	Industrial	8.0"	3.0"	1.0"	4.65"	4.16"	4.5"	1,968' (600 m)	CSI	1.0"

***Any information published deemed reliable but not guaranteed. Please refer to the manufacturer's documentation for more information.***



*Able Label stocks 4" O.D. or 5" O.D. by 1" Core label rolls which can be used with printer models with a maximum roll O.D. of 5.0".  
Able Label can also provide all of our products on any core, O.D. or wind direction desired. Call 800.348.1455 for quote.*

DATAMAX PRINTERS			MEDIA/LABEL SPECIFICATIONS (O.D.: OUTSIDE DIAMETER ~ I.D.: INSIDE DIAMETER)					RIBBON SPECIFICATIONS			
Model	Print Method	Printer Type	Maximum Roll O.D.	Core I.D.	Min Width	Max Width	Max Print Width	Max Width	Max Length	Ink Wind	Core I.D.
I-4406	DT or TT	Industrial	8.0"	3.0"	1.0"	4.65"	4.10"	4.5"	1,968' (600 m)	CSI	1.0"
I-4604	DT or TT	Industrial	8.0"	3.0"	1.0"	4.65"	4.16"	4.5"	1,968' (600 m)	CSI	1.0"
M-4206 Mark II	DT or TT	Industrial	8.0"	3.0"	0.75"	4.65"	4.25"	4.5"	1,476' (450 m)	CSI or CSO	1.0"
M-4210 Mark II	DT or TT	Industrial	8.0"	3.0"	0.75"	4.65"	4.25"	4.5"	1,476' (450 m)	CSI or CSO	1.0"
M-4308 Mark II	DT or TT	Industrial	8.0"	3.0"	0.75"	4.65"	4.25"	4.5"	1,476' (450 m)	CSI or CSO	1.0"
M-4206 (non Mark II)	DT or TT	Industrial	8.0"	3.0"	0.75"	4.65"	4.25"	4.5"	1,476' (450 m)	CSI	1.0"
M-4208	DT or TT	Industrial	8.0"	3.0"	0.75"	4.65"	4.25"	4.5"	1,476' (450 m)	CSI	1.0"
M-4306	DT or TT	Industrial	8.0"	3.0"	0.75"	4.65"	4.16"	4.5"	1,476' (450 m)	CSI	1.0"
p1115 Performance Series	DT or TT	Industrial	8.0"	3.0"	1.0"	4.65"	4.16"	4.65"	1,968' (600 m)	CSI or CSO	1.0"
p1115s Performance Series	DT or TT	Industrial	8.0"	3.0"	1.0"	4.65"	4.16"	4.65"	1,968' (600 m)	CSI or CSO	1.0"
p1125 Performance Series	DT or TT	Industrial	8.0"	3.0"	1.0"	4.65"	4.27"	4.65"	1,968' (600 m)	CSI or CSO	1.0"
p1725 Performance Series	DT or TT	Industrial	8.0"	3.0"	2.0"	7.1"	6.83"	7.1"	1,968' (600 m)	CSI or CSO	1.0"
p1120n Performance Series	DT or TT	Industrial	8.0"	3.0"	1.0"	4.65"	4.27"	4.65"	1,968' (600 m)	Near-Edge CSI or CSO	1.0"
Prodigy	DT or TT	Industrial	8.0"	3.0"	0.75"	4.65"	4.4"	4.5"	1,181' (360 m)	CSI	1.0"
Prodigy Max	DT or TT	Industrial	8.0"	3.0"	0.75"	4.65"	4.1"	4.5"	1,476' (450 m)	CSI	1.0"
Prodigy Plus	DT or TT	Industrial	8.0"	3.0"	0.75"	4.65"	4.1"	4.5"	1,181' (360 m)	CSI	1.0"
Titan 6200	DT or TT	Industrial	8.0"	3.0"	2.0"	6.7"	6.6"	6.7"	1,509' (460 m)	CSI	1.0"
W-6208	DT or TT	Industrial	8.0"	3.0"	2.0"	6.7"	6.62"	6.7"	1,509' (460 m)	CSI	1.0"
W-6308	DT or TT	Industrial	8.0"	3.0"	2.0"	6.7"	6.4"	6.7"	1,509' (460 m)	CSI	1.0"
W-8306	DT or TT	Industrial	8.0"	3.0"	3.0"	9.0"	8.53"	9.0"	1,509' (460 m)	CSI	1.0"
XL	DT or TT	Industrial	8.0"	3.0"	1.0"	4.65"	4.1"	4.5"	1,181' (360 m)	CSI	1.0"

***Any information published deemed reliable but not guaranteed. Please refer to the manufacturer's documentation for more information.***



Able Label stocks 4" O.D. or 5" O.D. by 1" Core label rolls which can be used with printer models with a maximum roll O.D. of 5.0".  
 Able Label can also provide all of our products on any core, O.D. or wind direction desired. Call 800.348.1455 for quote.

Model	Print Method	Printer Type	MEDIA/LABEL SPECIFICATIONS (O.D.: OUTSIDE DIAMETER ~ I.D.: INSIDE DIAMETER)					RIBBON SPECIFICATIONS				
			Maximum Roll O.D.	Core I.D.	Min Width	Max Width	Max Print Width	Max Width	Max Length	Ink Wind	Core I.D.	
Ovation 2	DT or TT	Desktop	4.0"	1.0"	1.0"	4.65"	4.1"	4.3"	361' (110 m)	CSI	0.5"	
E-4204B Mark III	DT or TT	Desktop	5.0"	1.0"	0.75"	4.4"	4.25"	4.3"	2.6" O.D.	CSI or CSO	0.5" or 1.0" w/ adaptors	
E-4304B Mark III	DT or TT	Desktop	5.0"	1.0"	0.75"	4.4"	4.16"	4.3"	2.6" O.D.	CSI or CSO	0.5" or 1.0" w/ adaptors	
E-4205A Mark III	DT or TT	Desktop	5.0"	1.0"	0.75"	4.4"	4.25"	4.3"	2.6" O.D.	CSI or CSO	0.5" or 1.0" w/ adaptors	
E-4305A Mark III	DT or TT	Desktop	5.0"	1.0"	0.75"	4.4"	4.16"	4.3"	2.6" O.D.	CSI or CSO	0.5" or 1.0" w/ adaptors	
E-4206P Mark III	DT or TT	Desktop	5.0"	1.0"	0.75"	4.4"	4.25"	4.3"	2.6" O.D.	CSI or CSO	0.5" or 1.0" w/ adaptors	
E-4305P Mark III	DT or TT	Desktop	5.0"	1.0"	0.75"	4.4"	4.16"	4.3"	2.6" O.D.	CSI or CSO	0.5" or 1.0" w/ adaptors	
E-4206L Mark III	DT or TT	Desktop	7.2"	1.0"	0.75"	4.4"	4.25"	4.3"	2.6" O.D.	CSI or CSO	0.5" or 1.0" w/ adaptors	
E-4305L Mark III	DT or TT	Desktop	7.2"	1.0"	0.75"	4.4"	4.16"	4.3"	2.6" O.D.	CSI or CSO	0.5" or 1.0" w/ adaptors	
E-Class Mark II	DT or TT	Desktop	5.0"	1.0"	0.75"	4.3"	~	4.3"	361' (110 m)	CSI	0.5"	
E-4205e Mark II	DT or TT	Desktop	5.0"	1.0"	0.75"	4.3"	4.25"	4.3"	361' (110 m)	CSI	0.5"	
E-4304e Mark II	DT or TT	Desktop	5.0"	1.0"	0.75"	4.3"	4.12"	4.3"	361' (110 m)	CSI	0.5"	
E-4203	DT or TT	Desktop	4.0"	1.0"	1.0"	4.3"	4.0"	4.3"	361' (110 m)	CSI	0.5"	
E-4204	DT or TT	Desktop	5.0"	1.0"	1.0"	4.3"	4.0"	4.3"	361' (110 m)	CSI	0.5"	
E-4304	DT or TT	Desktop	5.0"	1.0"	1.0"	4.3"	4.0"	4.3"	361' (110 m)	CSI	0.5"	
w1110 Workstation	DT ONLY	Desktop	5.0"	1.0" or 1.5"	0.75"	4.33"	4.16"	Not Required				
OC3	DT ONLY	Mobile	2.25"	0.75"	0.75"	3.0"	2.84"	Not Required				
LP3	DT ONLY	Mobile	3.5"	1.0"	1.0"	3.0"	2.84"	Not Required				
RL3e	DT ONLY	Mobile	2.65"	0.75"	1.0"	3.125"	2.8"	Not Required				

Any information published deemed reliable but not guaranteed. Please refer to the manufacturer's documentation for more information.



*Able Label stocks 4" O.D. or 5" O.D. by 1" Core label rolls which can be used with printer models with a maximum roll O.D. of 5.0".  
Able Label can also provide all of our products on any core, O.D. or wind direction desired. Call 800.348.1455 for quote.*

DATAMAX PRINTERS			MEDIA/LABEL SPECIFICATIONS (O.D.: OUTSIDE DIAMETER ~ I.D.: INSIDE DIAMETER)					RIBBON SPECIFICATIONS			
Model	Print Method	Printer Type	Maximum Roll O.D.	Core I.D.	Min Width	Max Width	Max Print Width	Max Width	Max Length	Ink Wind	Core I.D.
RL4e	DT ONLY	Mobile	2.65"	0.75"	2.0"	4.12"	4.125"	Not Required			
RP2	DT ONLY	Mobile	2.25"	0.75"	1.0"	2.25"	1.89"	Not Required			
RP4	DT ONLY	Mobile	2.25"	0.75"	2.0"	4.4"	4.1"	Not Required			
MP Nova 4 Mark II DT	DT ONLY	Ultra Compact	8.5"	1.5"	1.5"	4.5"	4.1"	Not Required			
MP Nova 4 Mark II TT	TT & DT	Ultra Compact	8.5"	1.5"	1.5"	4.5"	4.1"	4.33"	984' (300 m)	CSI or CSO	1.0"
MP Nova 6 Mark II DT	DT ONLY	Ultra Compact	8.5"	1.5"	1.5"	7.1"	6.6"	Not Required			
MP Nova 6 Mark II TT	TT & DT	Ultra Compact	8.5"	1.5"	1.5"	7.1"	6.6"	6.875"	984' (300 m)	CSI or CSO	1.0"
MP Compact 4 Mark III	DT ONLY	Ultra Compact	5.9"	Min 1.57"	1.6"	4.5"	4.1"	Not Required			
MP Compact 4 Mobile Mark III	DT ONLY	Ultra Compact	3.9"	Min 1.57"	1.6"	4.5"	4.1"	Not Required			

*Any information published deemed reliable but not guaranteed. Please refer to the manufacturer's documentation for more information.*